



CENTRAL VACUUM CLEANER DATA

Model	£390.00 Studio S80	£420.00 Studio S100	£525.00 Studio S150	£599.00 Studio S250			
Order number:	S80 Low voltage Trip	S100 Low Voltage Trip	S150 Low Voltage Trip	S250 Low Voltage Trip			
Motordata:							
Volt	230 Volt	230 Volt	230 Volt	230 Volt			
50 Hz	50 Hz	50 Hz	50 Hz	50 Hz			
KW	1.26	1.26	1.28	1.43			
Turbines	2-stage	2-stage	2-stage	2-stage			
Performance data:							
Max. Low pressure	2830mm WS	2830mm WS	2540mm WS	3130mm WS			
Max. airflow rate	211 m³/h	211 m³/h	190 m³/h	170 m³/h			
Max. Air watts	504	504	360	420			
Operative current	24 Volt	24 Volt	24 Volt	24 Volt			
Max. Furthest run	25m	25m	30m	40m			
Max. No. Inlets	5	6	8	12			
Cleaning Coverage	150m²	200m²	250m²	400m²			
Measurements:							
Height	580mm	900mm	1030mm	1030mm			
Diameter	280mm	280mm	320mm	320mm			
Weight							
Sound level DIN EN ISO 3744	65dBA	65 dBA	64dBA	64dBA			
Dust bin capacity	15 Liter	15 Liter	23 Liter	23 Liter			
Color	RAL 5002, RAL 9005	RAL 5002, RAL 9005	RAL 5002, RAL 9005	RAL 5002, RAL 9005			
Filter data:							
Filter	washable Polyester cartridge < 0.2 µ	washable Polyester - Filter < 0.2 µ	washable Polyester - Filter < 0.2 µ	washable Polyester - Filter < 0.2 µ			
Filter Surface	0.4 m²	0.7 m²	0.7 m²	0.7 m²			
User / Users	1	1	1	1			